

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: EVERGLUE AKTIVATOR

This safety data sheet pertains to the following products:

650006 Everglue Aktivator Spray, Aushärtungsbeschleuniger für Sekundenkleber, Aerosol
650066 Big Difference Aktivator Spray, Aushärtungsbeschleuniger für Sekundenkleber,
Aerosol

UFI: 8Q00-709J-Q00G-43KP

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: activator for adhesives

1.3 Details of the supplier of the safety data sheet

Company name: WIKO Klebetechnik Sp. z o.o.

Street/POB-No.: ul. Ekonomiczna 8

Postal Code, city: PL-42-271 Czestochowa

WWW: www.gluetec-group.com

E-mail: info.pl@gluetec-group.com

Telephone: +48 (0) 34 372 58 58

Telefax: +48 (0) 34 371 11 14

Department responsible for information:

Telephone: +48 (0) 34 372 58 58, E-mail: info.pl@gluetec-group.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen, Germany,

Telephone: +49 551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

(EUH066) Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)

Signal word: **Danger**

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 6/3/2026
Version: 4.0
Replaces version: 3.1
Language: en-IE
Date of print: 24/3/2026

EVERGLUE AKTIVATOR

Material number 650006_650066

Page: 2 of 13

Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements:	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing spray.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P405	Store locked up.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains Acetone.

2.3 Other hazards

Higher doses may lead to a narcotic effect.
Rapid evaporating can produce frostbites.
Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions:

Hazardous ingredients:

Identifiers	Designation Classification	Content
EC No. 200-662-2 CAS 67-64-1	Acetone Flam. Liq. 2; H225. Eye Irrit. 2; H319. STOT SE 3; H336. (EUH066).	< 60 %
EC No. 203-448-7 CAS 106-97-8	Butane Flam. Gas 1; H220.	< 20 %
EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220.	< 20 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!
In case of inhalation:	Provide fresh air. In the event of discomfort seek medical treatment.
Following skin contact:	Thoroughly wash skin with soap and water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Do not induce vomiting. Rinse mouth and seek medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:	Extinguishing powder, carbon dioxide, alcohol resistant foam.
Extinguishing media which must not be used for safety reasons:	Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.
May form dangerous gases and vapours in case of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid breathing spray. Avoid contact with the substance. In case of leakage, eliminate all ignition sources. Provide adequate ventilation.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid breathing spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.

Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

7.2 Conditions for safe storage, including any incompatibilities**Requirements for storerooms and containers:**

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values:**

CAS No.	Designation	Type	Limit value
67-64-1	Acetone	Europe: IOELV: TWA	1,210 mg/m ³ ; 500 ppm
		Ireland: 8 hours	1,210 mg/m ³ ; 500 ppm
106-97-8	Butane	Ireland: 8 hours	1,000 ppm

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment**Occupational exposure controls****Respiratory protection:**

In case of inadequate ventilation wear respiratory protection.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection:

Protective gloves according to I.S. EN ISO 374-1.
Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness: ≥ 0.5 mm
Breakthrough time: > 240 min
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection:

Tightly sealed goggles according to I.S. EN ISO 16321-1.

Body protection:

Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

Avoid breathing spray. Do not get in eyes, on skin, or on clothing.

When using do not eat or drink. Contaminated work clothing should not be allowed out of the workplace.

Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.

Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	Form: Aerosol colourless
Odour:	Characteristic
Melting point/freezing point:	No data available
Boiling point:	No data available
Flammability:	Extremely flammable aerosol.
Lower and upper explosion limit:	LEL (Lower Explosion Limit): 1.40 Vol-% UEL (Upper Explosive Limit): 8.40 Vol-%
Flash point:	-47 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Kinematic viscosity:	No data available
Solubility:	Soluble in: Ethanol, ether
Partition coefficient n-octanol/water (log value):	No data available
Vapour pressure:	No data available
Density:	No data available
Relative vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	393 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties:

No data available

Other information:

Information about Acetone (CAS 67-64-1):
LD50 Rat, oral: 5,800 mg/kg
LD50 Rabbit, dermal: 7,400 mg/kg
LC50 Rat, inhalative: 76 mg/L 4h

Symptoms

In high concentrations may cause asphyxiation.

Vapours of organic solvents may have a narcotic effect.

Other symptoms: Agitation, spasms, cardiac arrhythmias.

In case of inhalation: Mucous membrane irritation, cough and shortage of breath.

After contact with skin:
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Further details: No data available

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances.

* = Evidence for disposal must be provided.

Recommendation: Special waste. Do not open with force or incinerate, even when empty.
Do not dispose of with household waste. Do not allow product to reach sewage system.
Dispose of waste according to applicable legislation.**Package**

Waste key number: 15 01 04 = Metallic packaging.

Recommendation: Empty carefully and completely, if possible.
Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.**Section 14. Transport information****14.1 UN number or ID number**

ADR/RID, IMDG, IATA-DGR:

UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS

IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F
IMDG: Class 2, Subrisk -, see SP63
IATA-DGR: Class 2.1



14.4 Packing group

ADR/RID, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally
hazardous according to the criteria of the UN
model regulations.

Marine pollutant: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: RID: Hazard identification number 23, UN number UN 1950
Hazard label: 2.1
Special Provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Package - Instructions: P207 LP200
Package - Special Provisions: PP87 RR6 L2
Special provisions for packing together: MP9
Tunnel restriction code: D

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: See SP277
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label:	Flamm. gas
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions:	A145 A167 A802
Emergency Response Guide-Code (ERG):	10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - EC member states****Labelling of packaging with <= 125mL content**

Signal word:	Danger
Hazard statements:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements:	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P271 Use only outdoors or in a well-ventilated area. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container to hazardous or special waste collection point.

Further regulations, limitations and legal requirements:

Product:	Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg Use restriction according to REACH annex XVII, no.: 3, 40, 75 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P3a
Acetone:	Regulation (EU) 2019/1148 (marketing and use of explosives precursors): listed REGULATION (EC) 273/2004 (Drug precursors): Category 3 REGULATION (EC) 111/2005 (Trade with drug precursors): Category 3

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H222 = Extremely flammable aerosol.
H229 = Pressurised container: May burst if heated.
H319 = Causes serious eye irritation.
H336 = May cause drowsiness or dizziness.
EUH066 = Repeated exposure may cause skin dryness or cracking.
H225 = Highly flammable liquid and vapour.
H220 = Extremely flammable gas.

Reason of change: Changes in section 1.3: address, E-mail, telephone, Department responsible for information
Changes in section 1.4: emergency telephone number

Date of first version: 25/8/2021

Department issuing data sheet:
see section 1: Department responsible for information

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aerosol: Aerosol
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
EU: European Union
Eye Irrit.: Eye irritation
Flam. Gas: Flammable gases
Flam. Liq.: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)
2020/878

EVERGLUE AKTIVATOR

Material number 650006_650066

Revision date: 6/3/2026
Version: 4.0
Replaces version: 3.1
Language: en-IE
Date of print: 24/3/2026

Page: 13 of 13

Most recent product information is available at:
<https://sumdat.net/tgpbxvur>

